

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 April 2005 (21.04.2005)

PCT

(10) International Publication Number
WO 2005/035127 A1

(51) International Patent Classification⁷: **B02C 19/06**,
23/00, 25/00

(21) International Application Number:
PCT/FI2003/000750

(22) International Filing Date: 10 October 2003 (10.10.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(71) Applicant (for all designated States except US):
MICROPULVA LTD OY [FI/FI]; Haavistontie 27,
FIN-33960 Pirkkala (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): NIEMI, Jouko
[FI/FI]; Haavistontie 27, FIN-33960 Pirkkala (FI). TAM-
MINEN, Jarkko [FI/FI]; Automiehenkatu 3 D, FIN-33840
Tampere (FI).

(74) Agent: NIEMINEN, Taisto; Patenttitoimisto T Nieminen
Oy, Kehräsaari B, FIN-33200 Tampere (FI).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD FOR INDUSTRIAL PRODUCING OF HIGHLY DISPERSED POWDERS



(57) Abstract: This invention relates to industrial production of fine dispersed powders, where the material to be pulverized is mixed with high-pressure working into a gas-solids suspension, which through acceleration nozzles (8) is conveyed to the pulverizing chamber of counterjet pulverizer (9) for autogenous pulverization. The method is known in that the pulverized gas-solids suspension is conveyed in the pulverizing circle at least to one intermediate tank (12), where the gas is removed from the blend and solids are collected into intermediate tank (12), which are returned together with new raw material for pulverization till in the equipment a wanted circulation load is achieved, whereafter the process continues so that from it as much ready product is removed as new material is added to it.